

Ohio Paperboard



Location:

Baltimore, OH

Trim:

135"

Caliper Range:

✓ .008" – .025"

Caliper Range	Min Trim	Max Trim
.008 – .015	114	132
.016 – .025	115	135

Rolls:

- ✓ Widths 2" or greater
- ✓ 40" – 76" diameters
- ✓ 3", 4", 8" and 12" cores
- ✓ Ribbon slit tolerance: $\pm 1/32$ "

Certifications:

- ✓ FSC[®], SFI[®] and PEFC[®] Chain of Custody Standard for Recycled Paper
- ✓ FDA[®] Compliant for Dry Food Packaging
 - 21 CFR 176.170
 - 21 CFR 176.18
 - 21 CFR 176.260
- ✓ RPTA 100% Certified

Product Offerings:

- ✓ NewKraft Release
 - 2-sided sheet, only one side is absorbent
 - Used for high pressure laminates
- ✓ Saturating Kraft
 - Used in inner pile of high pressure laminates
- ✓ Top Ply
- ✓ Tubing Grades
 - Ultra 100 and 200
 - High Sized
- ✓ Flextan[®] (Tan Bending Chip)
- ✓ Non-Test Liner
- ✓ LinerBoard
- ✓ Partition
- ✓ Plain Chip
- ✓ High Pressure Laminate (HPL) Grades
- ✓ Release Liner/Saturating Kraft Grades Available

Ohio Paperboard *page 2*

Available Grades

	Density	Caliper	Basis Wt
Tube & Core Grades – Wet or Dry Finishes			
Ultra 100	3.1 – 3.8	11pt – 25pt	28# – 81#
Ultra 200	3.3 – 3.4	14pt – 19pt	44# – 62#
Chip Grades			
Flextan Bending Chip	3.5 – 3.9	12pt – 22pt	44# – 84#
Partition Chip	3.1 – 3.5	12pt – 24pt	44# – 84#
Plain Chip	3.3 – 3.6	8pt – 20pt	29# – 84#
Top Ply Grades			
Top Ply Available in Water, Dry or Sized Finishes	3.4 – 3.9	10pt – 20pt	30# – 70#

Converting Capabilities

Slitters (2)	
Sizes	Calipers
Min. diameter: 40"	Min.: .008
Max. diameter: 60"	Max.: .025
Minimum Slit Width: 2"	
Slitter Specs	
Minimum ribbon width: 4"	
Maximum roll width: 96"	

📍 For more information: 1-800-858-1438