



IBC

# ***GCUBE<sup>®</sup> IBC Elektron***

***One of the Safest Solutions for EX Zones 1+2***

Uses multi-layer technology approved for EX zones.

# **GREIF<sup>®</sup>**

PACKAGING SUCCESS TOGETHER

[www.greif.com](http://www.greif.com)

# GCUBE® IBC Elektron Features

- ✓ 6" (150 mm) and 9" (225 mm) openings available with all types of ventilation with hybrid or wooden pallets.
- ✓ 2" and 3" valves with over-coated HDPE layer which ensures that only one material comes in contact with filled products.
- ✓ GCUBE® Elektron is also available with antistatic additive for food contact (GCUBE® Food) and with barrier properties to prevent gas permeation (GCUBE® Shield).
- ✓ GCUBE® Hybrid Pallet helps promote effective movement along the conveyors for faster filling.



## High Performance

With special additives in co-extrusion technology, the outer layer has an antistatic surface and the discharging valve, produced with conductive PE, is grounded through the cage and the pallet.



## GCUBE® Elektron Is Compliant with Regulations Pertaining to EX Zones

GCUBE® Elektron is compliant with EN 50014 and is suitable for EX zones 1+2 (CENELEC Technical report 50404:2003).

📍 For more information, talk to your local sales representative.